

PACE[®] Model 203

DUAL CHAMBER (DDD)
TEMPORARY CARDIAC PACEMAKER



Now available with
terminals for bipolar
connectors

PACE® Model 203 Highlights

- Constant voltage output for reliable cardiac capture (similar to permanent pacemakers)
- In Control: The first external pacemaker to instantly show the voltage (Volts) and current (mA) applied to the patient along with the impedance of the lead system (U.S. Patent 9,433,794)
- Check the quality and placement of the lead system (e.g., pacing wires)
- Ideally, the impedance of the lead system should be between 200 and 2,000 Ohms
- Low impedance can be caused if stimulation electrodes are placed in close proximity or have a large surface area (loss of capture)
- High impedance may indicate a compromised connection or disconnected lead
- P and R Wave amplitudes measured upon pressing PAUSE key
- Quick and easy change of battery: no need to worry about battery orientation (one single 9 V battery)
- Lifetime service
- Different connection versions available, collets for unipolar exposed pins (Ø 0.9 to 2.0 mm) and sockets for bipolar plugs



Specifications

PACE® Model 203

| | | |
|---------------------------|----------------------------------------------------------------------|----------------------------------------------------------------|
| Modes | DDD, VVI, AAI, VDD D00, V00, A00, DVI, DAI, VAT, AAT, DDD+AT, DAT | |
| Basic Pacing Rates | 30 – 220 ppm | |
| Rapid Atrial Pacing Rates | 70 – 1,000 ppm | |
| Output Amplitude | 0.1 – 18 V | |
| Pulse Width | 0.05 – 1.5 ms | |
| Sensitivity Threshold | Atrium : 0.2 – 20 mV | Ventricle: 1.0 – 20 mV |
| Refractory Period | 250 ms | |
| Dimensions | P/N 2002: 21.7 cm x 9.6 cm x 5.1 cm (8.9" x 3.8" x 2.0") | P/N 2003: 21.2 cm x 9.6 cm x 5.1 cm (8.3" x 3.8" x 2.0") |
| Weight incl. Battery | 490 g (17.3 ounces) | |
| Battery Type | 9V Type 6LP3146 Alkaline | |
| Battery Life | Alkaline: Up to 10 days (72 ppm, 8.0V) | |

Products and options may not be available in every region or country. Please contact mail@osypkamed.com for availability in your region and country and for further information.

Osypka Medical GmbH

Albert-Einstein-Strasse 3
12489 Berlin, Germany
Phone: +49 (30) 6392 8300
Fax: +49 (30) 6392 8301
E-Mail: mail@osypkamed.com
www.osypkamed.com

United States of America:
Osypka Medical, Inc.

dba. Cardiotronic
La Jolla, CA 92037, USA
Phone: +1 (858) 454 0600
Fax: +1 (858) 454 0640
E-Mail: mail@cardiotronic.net
www.cardiotronic.net

PACE and the logos are
trademarks of Osypka Medical.



Copyright © 2024 Osypka Medical